

MODEL LBP-WS

BRIDGE PLUG - WIRELINE SET

The Model LBP-WS Cast Iron Drillable Bridge Plug's modular, field proven design makes it a versatile tool in a variety of applications. The LBP-WS may be set on a wireline setting tool or set mechanically by changing the top slips. The LBP-WS also converts to a LCR-WS Cement Retainer by replacing the solid plug with a sleeve valve.

APPLICATIONS:

- Well Abandonment
- Temporary or Permanent zone isolation

FEATURES, ADVANTAGES, AND BENEFITS:

- Cast iron drillable design
- Converts between mechanical or wireline set by changing top slips
- Converts to a Model LCR Cement Retainer
- Temperature rating to 325° F
- Differential pressure rating to 10,000 psi thru 7 5/8"
- Convertibility reduces inventory requirements
- Fast drill out saves rig time

| SPECIFICATIONS | | | | | |
|----------------|--------------|--------------|--------|---------------|--------|
| CASING | | PLUG | | SETTING RANGE | |
| OD | WT. (LBS/FT) | PART NUMBER | OD | MIN. | MAX. |
| 4 1/2 | 9.5 - 16.6 | 005-3593-003 | 3.593 | 3.826 | 4.090 |
| 5 | 11.5 - 18 | 005-3937-003 | 3.937 | 4.154 | 4.560 |
| 5 1/2 | 13 - 23 | 005-4312-003 | 4.312 | 4.580 | 5.044 |
| 6 | 10.5 - 12 | 005-5375-003 | 5.375 | 5.959 | 6.135 |
| 6 5/8 | 17 - 34 | 005-5375-003 | 5.375 | 5.959 | 6.135 |
| 7 | 32 - 38 | 005-5375-003 | 5.375 | 5.959 | 6.135 |
| 7 | 17 - 35 | 005-5687-003 | 5.687 | 6.004 | 6.538 |
| 7 5/8 | 20 - 39 | 005-6312-003 | 6.312 | 6.625 | 7.263 |
| 8 5/8 | 24 - 49 | 005-7125-003 | 7.125 | 7.511 | 8.248 |
| 9 5/8 | 29.3 - 53.5 | 005-8125-003 | 8.125 | 8.435 | 9.063 |
| 10 3/4 | 54 - 81 | 005-9000-003 | 9.000 | 9.250 | 9.660 |
| 10 3/4 | 32.7 - 51 | 005-9437-003 | 9.437 | 9.660 | 10.192 |
| 13 3/8 | 77 - 102 | 005-1156-003 | 11.562 | 11.633 | 12.464 |
| 13 3/8 | 48 - 72 | 005-1200-003 | 12.000 | 12.175 | 12.715 |

